

# POWER WD 80.2 P CF



WET & DRY VACUUM CLEANERS  
WITH INTEGRATED DISCHARGING PUMP

High efficiency, trolley mounted wet & dry vacuum unit, equipped with an integrated discharging pump for continuous suction/dumping. Model equipped with the UFS System (Ultra FilteRing System) that, thanks to its special polypropylene spacer ring, allows to keep the cartridge filter (M filtration class) always installed guaranteeing best suction performances and maximum motor protection (even in case of incorrect use by the operator). UFS is also a practical solution: the floating system is independent from the motor head, making cleaning and maintenance quick, simple and intuitive. This unique machine's performances are very suitable for civil/emergency service, contract cleaners and fire brigades. It can be used also as a normal dry or wet & dry vacuum cleaner.



Ultra FilteRing System



PTFE cartridge filter (M filtration class)



Discharging pump



Exhaust air filter



Intake + socket for discharging pump

## PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
POWER WD 80.2 P CF	14491210001	1

## TECHNICAL DATA

Voltage - Frequency	220-240 V~	50/60 Hz
Max power rating	W	2500
Rated power (nominal power)	W	2200
Container capacity	l	80
Useful capacity	l	42
Air flow rate	l/s	142
Vacuum	mbar	225
Sound level	db(A)	62
IP code		IPX4
Power supply cable	m	10
Weight (without accessories)	Kg	32,5
Dimensions	mm	740x580x1010
<b>DISCHARGING PUMP:</b>		
• Water flow	l/min	max 220
• Max power	W	370
• Lift performance		max 8 m (flow 20 l/min)

## STANDARD ACCESSORIES

TYPE	REF. NO.
Flexible hose 2,5 m	6010500
Suction tube "S"	2511600
Squeegee tool	6010011
Crevice tool	2511610
PTFE cartridge filter (M filtration class)	2512742

Ø 40

## OPTIONAL ACCESSORIES

TYPE	REF. NO.
Nylon protection filter	3001009
HEPA cartridge filter (filtering surface 1,20 m <sup>2</sup> )	2512761
TNT filter	6830015
Paper filter bag with cap l 19 x 10	6830030